

ODE-3-120070-1012

Optidrive E3 VFD Datasheet

1.5 kW (2 HP), 7 A, 200-240 V, 1-3PH
IP20 Variable Frequency Drive



Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 200-240 V |
| Input Phases | 1 |
| Supply Current Continuous | 12.9 A |
| Supply Fuse or MCB (Type B) | 16 A |

Output Ratings

| | |
|---------------------|--------------------|
| Motor Output Rating | 1.5 kW (2 HP) |
| Output Voltage | 0 – Supply Voltage |
| Output Current | 7 A |

Cable Information

| | |
|------------------------|--------------------------------|
| Max Supply Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft) |

Factory Build Options

| | |
|------------------|------------------------------|
| EMC Filter | No Internal EMC Filter |
| Brake Transistor | No Internal Brake Transistor |
| Enclosure | IP20 |
| Display | LED |



Buy this drive or get more information:
<https://www.shc-gmbh.com>

Drive Dimensions

| | |
|---------|------------------|
| Size | 1 |
| Height | 173 mm (6.81 in) |
| Width | 83 mm (3.27 in) |
| Depth | 123 mm (4.84 in) |
| Weight | 1 kg (2.2 lbs) |
| Fixings | 4 x M5 |

Packaged Dimensions

| | |
|--------|-------------------|
| Height | 165 mm (6.5 in) |
| Width | 125 mm (4.92 in) |
| Depth | 235 mm (9.25 in) |
| Weight | 1.2 kg (2.65 lbs) |

