

# ODE-3-210058-104B

## Optidrive E3 VFD Datasheet

### 1.1 kW (1.5 HP), 5.8 A, 110-115 V, 1-3PH

IP66 Outdoor Switched Variable Frequency Drive



#### Input Ratings

Supply Voltage	110-115 V
Input Phases	1
Supply Current Continuous	21.9 A
Supply Fuse or MCB (Type B)	32 A

#### Output Ratings

Motor Output Rating	1.1 kW (1.5 HP)
Output Voltage	0 – 2 x Supply Voltage
Output Current	5.8 A

#### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Enclosure	IP66 Outdoor Switched
Display	LED



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

#### Drive Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	182 mm (7.17 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

#### Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)

