

ODE-3-320153-1042

Optidrive E3 VFD Datasheet

4 kW (5 HP), 15.3 A, 200-240 V, 1-3PH
IP20 Variable Frequency Drive



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	29.2 A
Supply Fuse or MCB (Type B)	40 A

Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	15.3 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Enclosure	IP20
Display	LED



Buy this drive or get more information:
<https://www.shc-gmbh.com>

Drive Dimensions

Size	3
Height	261 mm (10.28 in)
Width	131 mm (5.16 in)
Depth	175 mm (6.89 in)
Weight	3.2 kg (7.05 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	254 mm (10 in)
Width	162 mm (6.38 in)
Depth	315 mm (12.4 in)
Weight	3.5 kg (7.72 lbs)

