

ODP-2-22220-3KF4B-MN

Optidrive P2 VFD Datasheet

2.2 kW, 10.5 A, 200-240 V, 3PH

IP66 Switched Outdoor Variable Frequency Drive with EMC Filter and TFT Display



Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 200-240 V |
| Input Phases | 3 |
| Supply Current Continuous | 12.6 A |
| Supply Fuse or MCB (Type B) | 16 A |

Output Ratings

| | |
|---------------------|--------------------|
| Motor Output Rating | 2.2 kW (3 HP) |
| Output Voltage | 0 – Supply Voltage |
| Output Current | 10.5 A |

Cable Information

| | |
|------------------------|--------------------------------|
| Max Supply Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft) |

Factory Build Options

| | |
|------------------|-----------------------|
| EMC Filter | Internal EMC |
| Brake Transistor | Internal |
| Enclosure | IP66 Switched Outdoor |
| Display | TFT Display |
| PCB Coating | Standard |



Drive Dimensions

| | |
|---------|-------------------|
| Size | 2 |
| Height | 257 mm (10.12 in) |
| Width | 188 mm (7.4 in) |
| Depth | 172 mm (6.77 in) |
| Weight | 3.5 kg (7.72 lbs) |
| Fixings | 4 x M4 |

Packaged Dimensions

| | |
|--------|-------------------|
| Height | 215 mm (8.46 in) |
| Width | 235 mm (9.25 in) |
| Depth | 375 mm (14.76 in) |
| Weight | 4.2 kg (9.26 lbs) |



Buy this drive or get more information:
<https://www.shc-gmbh.com>

