

# ODP-2-62045-3KF42-MN

## Optidrive P2 VFD Datasheet

### 45 kW, 180 A, 200-240 V, 3PH

IP20 Variable Frequency Drive with EMC Filter and TFT Display



#### Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	163.4 A
Supply Fuse or MCB (Type B)	200 A

#### Output Ratings

Motor Output Rating	45 kW (60 HP)
Output Voltage	0 – Supply Voltage
Output Current	180 A

#### Cable Information

Max Supply Cable Size	150 mm <sup>2</sup> (0.23 sq in)
Max Motor Cable Size	150 mm <sup>2</sup> (0.23 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

#### Drive Dimensions

Size	6B
Height	726 mm (28.58 in)
Width	330 mm (12.99 in)
Depth	320 mm (12.6 in)
Weight	43 kg (94.8 lbs)
Fixings	-

#### Packaged Dimensions

Height	380 mm (14.96 in)
Width	375 mm (14.76 in)
Depth	785 mm (30.91 in)
Weight	46 kg (101.41 lbs)

