

# ODP-2-64075-3KF4N-MN

## Optidrive P2 VFD Datasheet

### 75 kW, 150 A, 380-480 V, 3PH

IP55 Variable Frequency Drive with EMC Filter and TFT Display



#### Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	144.1 A
Supply Fuse or MCB (Type B)	200 A

#### Output Ratings

Motor Output Rating	75 kW (120 HP)
Output Voltage	0 – Supply Voltage
Output Current	150 A

#### Cable Information

Max Supply Cable Size	150 mm <sup>2</sup> (0.23 sq in)
Max Motor Cable Size	150 mm <sup>2</sup> (0.23 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP55
Display	TFT Display
PCB Coating	Standard



#### Drive Dimensions

Size	6
Height	865 mm (34.06 in)
Width	330 mm (12.99 in)
Depth	332 mm (13.07 in)
Weight	55 kg (121.25 lbs)
Fixings	4 x M10

#### Packaged Dimensions

Height	980 mm (38.58 in)
Width	450 mm (17.72 in)
Depth	450 mm (17.72 in)
Weight	58 kg (127.87 lbs)



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

