

# ODV-3-460340-301A-MN

## Optidrive Eco VFD Datasheet

### 22 kW (30 HP), 34 A, 500-600 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive with TFT Display



#### Input Ratings

|                             |           |
|-----------------------------|-----------|
| Supply Voltage              | 500-600 V |
| Input Phases                | 3         |
| Supply Current Continuous   | 41.2 A    |
| Supply Fuse or MCB (Type B) | 50 A      |

#### Output Ratings

|                     |                    |
|---------------------|--------------------|
| Motor Output Rating | 22 kW (30 HP)      |
| Output Voltage      | 0 – Supply Voltage |
| Output Current      | 34 A               |

#### Cable Information

|                        |                                 |
|------------------------|---------------------------------|
| Max Supply Cable Size  | 16 mm <sup>2</sup> (0.02 sq in) |
| Max Motor Cable Size   | 16 mm <sup>2</sup> (0.02 sq in) |
| Max Motor Cable Length | 100 m (328 ft)                  |

#### Factory Build Options

|                  |                           |
|------------------|---------------------------|
| EMC Filter       | No Internal EMC           |
| Brake Transistor | No Brake Transistor       |
| Enclosure        | IP66 Non Switched Outdoor |
| Display          | TFT Display               |
| PCB Coating      | Standard                  |



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

#### Drive Dimensions

|         |                    |
|---------|--------------------|
| Size    | 4                  |
| Height  | 360 mm (14.17 in)  |
| Width   | 240 mm (9.45 in)   |
| Depth   | 261 mm (10.28 in)  |
| Weight  | 9.5 kg (20.94 lbs) |
| Fixings | 4 x M4             |

#### Packaged Dimensions

|        |                     |
|--------|---------------------|
| Height | 325 mm (12.8 in)    |
| Width  | 295 mm (11.61 in)   |
| Depth  | 425 mm (16.73 in)   |
| Weight | 11.5 kg (25.35 lbs) |

