

# ODV-3-621100-3F12-MN

## Optidrive Eco VFD Datasheet

### 30 kW (40 HP), 110 A, 200-240 V, 3PH

IP20 Variable Frequency Drive with EMC Filter and TFT Display



#### Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	97.8 A
Supply Fuse or MCB (Type B)	125 A

#### Output Ratings

Motor Output Rating	30 kW (40 HP)
Output Voltage	0 – Supply Voltage
Output Current	110 A

#### Cable Information

Max Supply Cable Size	150 mm <sup>2</sup> (0.23 sq in)
Max Motor Cable Size	150 mm <sup>2</sup> (0.23 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard



#### Drive Dimensions

Size	6A
Height	614 mm (24.17 in)
Width	286 mm (11.26 in)
Depth	320 mm (12.6 in)
Weight	32 kg (70.55 lbs)
Fixings	-

#### Packaged Dimensions

Height	380 mm (14.96 in)
Width	375 mm (14.76 in)
Depth	780 mm (30.71 in)
Weight	35 kg (77.16 lbs)



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

