


GL-series solid state input relay

- Plug-in input relay for 24 VDC voltage, polarity free
- 50 mA maximum load current
- 0...60 VDC load voltage
- Integrated status LED
- Works without logic supply (4 pole)
- For PLC input signal conditioning
- Shielded signal cabling not required
- CE (EMC and LVD)

Block diagram



Specifications (at temperature of 25 °C)

Primary

Input voltage	nominal	24 VDC
Input current	typical	6 mA
Input current at nominal voltage	maximum	7 mA
Input voltage range (abs.)	minimum	18,5 VDC
	maximum	32 VDC
Input impedance	typical	4 kΩ
Switch-on voltage	typical	16 VDC
	maximum	18,5 VDC
Switch-off voltage	typical	14 VDC
	minimum	12 VDC
Noise immunity	typical	60 μJ


Secondary

Load voltage	minimum	0 VDC
	maximum	60 VDC
Load current	maximum	50 mA
Voltage drop at max. load	typical	0,2 VDC
	maximum	0,4 VDC
Switch-on delay	typical	0,5 ms
	maximum	1 ms
Switch-off delay	maximum	0,5 ms
	maximum	1 ms

Physical dimensions and other data

Breakdown voltage I/O	Minimum	4300 VAC rms
Material	thermoplastic	UL 94 V-0
Weight	typical	30 g
Air/creepage distance I/O	minimum	8 mm
Capacitance I/O	typical	3 pF
Temperatures		
storage		-40 °C...+70 °C
operation		-25 °C...+70 °C

Color of casing: white



Dimensions in mm.

Temperature limitations

There are no limitations needs for this relay.

Derating when switching inductive loads

This relay is meant for PLC inputs and similar loads. A clamp diode must be used when switching inductive loads.

Fusing

To protect relay against short circuit and overload a fast fuse with the correct rating for the load and the capacity of the relay should be chosen. Note that when overload current is not large it is possible that the fuse will not protect the relay because of the tolerance on the fuse rating.

Approvals



Product has been designed to meet the main requirements of the EMC-directive 2004/108/EC. The secondary side of the relay has designed to operate up to specified low voltage levels, thus the relay does not comply with the high test voltages specified in the EN61000-4-5 standard.

The relay fulfils requirements of the low voltage directive 2006/95/EC.

Guarantee

The solid state I/O relays and accessories made by Delcon Oy are guaranteed free from design and manufacturing defects for a period of three years from the shipping date. For electromechanical relays the guarantee is one year. The guarantee liability is limited to replacement of defective material and related shipping charges. Defective materials must be returned to the manufacturer for evaluation. This guarantee does not cover damage due to incorrect use or electrical overload.

Delcon Oy
Veikkointie 4
03100 Nummela
Finland

Tel. +358 9 7771180
Fax +358 9 77711840
www.delcon.fi

9.3.2011