













Koppelrelais "Serie 1" (Printrelais)

interface relays "series 1" PCB - relays

	Bestellbezeichnung <i>ordering-key</i>	Spulenspannung <i>coil voltage</i>	Beschreibung <i>description</i>	Anschlussart <i>connection</i>	Technische Daten <i>technical data</i>		
	SHC112SD24G SHC112SA24R SHC112SA230R	24VDC 24VAC 230VAC	Koppelrelais mit Schraubanschlüssen <i>interface relays with screw terminals</i> 1-polig / 1-pole 16A/250VAC DC oder AC-Spulen <i>DC or AC coils</i> VPE <i>packaging</i> 10		Nennspannung <i>rated voltage</i> 250VAC Nennschaltleistung <i>switching load</i> 2.000/4.000VA Prüfspannung 5.000 Veff Spule-Kontakt <i>dielectric strength coil-contact</i> Luft-u.Kriechstrecke <i>clearance - creepage</i> > 10mm Umgebungstemperatur <i>ambient temperature</i> - 25..+70°C Schutzart <i>protection category</i> IP 20 Anschlußquerschnitt <i>wire cross section:</i> - Massiver Draht <i>single wire</i> 2 x 2,5 mm ² - Litzendraht <i>fine wire</i> 2 x 2,5 mm ² - Aderendhülse <i>wire end sleeve</i> 2 x 1,5 mm ² Schraubendrehmoment <i>screw torque</i> max. 0,7 Nm		
	SHC122SD24G SHC122SA24R SHC122SA230R	24VDC 24VAC 230VAC	Koppelrelais mit Schraubanschlüssen <i>interface relays with screw terminals</i> 2-polig / 2-pole 8A/250VAC DC oder AC-Spulen <i>DC or AC coils</i> VPE <i>packaging</i> 10				
	SHC113SD24G SHC113SA24R SHC113SA230R	24VDC 24VAC 230VAC	Koppelrelais mit Schraubanschlüssen <i>interface relays with screw terminals</i> 1-polig / 1-pole 16A/250VAC DC oder AC-Spulen <i>DC or AC coils</i> sichere Trennung Spule/Kontakt <i>safe insulation coil/contact</i> VPE <i>packaging</i> 10				
	SHC123SD24G SHC123SA24R SHC123SA230R	24VDC 24VAC 230VAC	Koppelrelais mit Schraubanschlüssen <i>interface relays with screw terminals</i> 2-polig / 2-pole 8A/250VAC DC oder AC-Spulen <i>DC or AC coils</i> sichere Trennung Spule/Kontakt <i>safe insulation coil/contact</i> VPE <i>packaging</i> 10				
	SHC113CD24G SHC113CA24R SHC113CA230R	24VDC 24VAC 230VAC	Koppelrelais mit Federzuganschlüssen <i>interface relays with screwless terminals</i> 1-polig / 1-pole 16A/250VAC DC oder AC-Spulen <i>DC or AC coils</i> sichere Trennung Spule/Kontakt <i>safe isolation coil/contact</i> VPE <i>packaging</i> 10				
	SHC123CD24G SHC123CA24R SHC123CA230R	24VDC 24VAC 230VAC	Koppelrelais mit Federzuganschlüssen <i>interface relays with screwless terminals</i> 2-polig / 2-pole 8A/250VAC DC oder AC-Spulen <i>DC or AC coils</i> sichere Trennung Spule/Kontakt <i>safe insulation coil/contact</i> VPE <i>packaging</i> 10				

R = LED Rot, bei AC - Spule + Varistor (LED Grün optional) / G = LED Grün, bei DC - Spule + FLD(+A1) (LED Rot optional)
 R = LED red, at AC - coil (LED green optional) / G = LED green, at DC - coil + protection diode(+A1) (LED red optional)