









Sockets for industrial relays



	Ordering Key	Description	Connection	Technical data
	PF-083BE	<ul style="list-style-type: none"> - Socket with screw terminals - 8-pole - For 2-pole industrial relays - Verpackungseinheit = 10 		<ul style="list-style-type: none"> Rated voltage: 300VAC Rated current: 12A
	PF-083BE/M	<ul style="list-style-type: none"> - Socket with screw terminals - 8-pole - For 2-pole industrial relays - For modules - Verpackungseinheit = 10 		<ul style="list-style-type: none"> Dielectric strength: > 2.500Veff Ambient temperature: - 25..+70°C Terminal screw torquet: 0,7 Nm Protection category: IP 20
	PF-113BE	<ul style="list-style-type: none"> - Socket with screw terminals - 11-pole - For 3-pole industrial relays - Verpackungseinheit = 10 		<ul style="list-style-type: none"> <i>Wire cross section</i> - Single wire: 2 x 2,5 mm²
	PF-113BE/M	<ul style="list-style-type: none"> - Socket with screw terminals - 11-pole - For 3-pole industrial relays - For modules - Verpackungseinheit = 10 		<ul style="list-style-type: none"> - Fine wire: 2 x 2,5 mm² - Wire end sleeve: 2 x 1,5 mm² Wire strip length: 10 mm

Approvals:

